

3196.2

STD-TS/LED(GN) GR

STD-TS/LED(GN) GR



Switchgear cabinet socket with LED, Mounting type: TS 35/7.5, Width: 45 mm, Colour: Grey

RAL: 7032

Business data

Product description	Switchgear cabinet socket with LED
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	69
Weight per piece (including packaging)	77.6
Unit of weight	G
Customs number	85369010
Country of origin	CN

3196.2

STD-TS/LED(GN) GR

STD-TS/LED(GN) GR

Technical Data

Dimensions

Length	75 mm
--------	-------

Width	45 mm
-------	-------

Height TS 35/7.5	67 mm
------------------	-------

Ratings

Rated voltage	250 AC V
---------------	----------

Rated current	16 AC A
---------------	---------

3196.2

STD-TS/LED(GN) GR

STD-TS/LED(GN) GR

Technical Data

Connection data

Wire cross-section single-core (rigid) / stranded, min.	0.2 mm ²
---	---------------------

Wire cross-section single core (rigid)/stranded, max.	4 mm ²
---	-------------------

Wire cross-section stranded, min.	0.2 mm ²
-----------------------------------	---------------------

Wire cross-section stranded, max.	2.5 mm ²
-----------------------------------	---------------------

Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
--	---------------------

Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
--	---------------------

Wire cross-section AWG, min.	24
------------------------------	----

Wire cross-section AWG, max.	12
------------------------------	----

Stripping length	8 mm
------------------	------

Screw threading	M 3
-----------------	-----

Tightening torque, min.	0.5 Nm
-------------------------	--------

Tightening torque, max.	1 Nm
-------------------------	------

Materials

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-0
--------------------------	-----

Working temperature, min.	-20 °C
---------------------------	--------

Working temperature, max.	60 °C
---------------------------	-------

Holding clip	Metal
--------------	-------

Further technical data

Illuminated display	LED, grün mit Vorwiderstand
---------------------	-----------------------------

3196.2

STD-TS/LED(GN) GR

STD-TS/LED(GN) GR

Approvals

Standards and regulations

Standards / specifications

Directive 2014/35/EU, DIN 49440-1:2006-01, DIN VDE
0620-1:2016-01

3196.2

STD-TS/LED(GN) GR

STD-TS/LED(GN) GR

Accessories

Marker



Device and installation markers / Maxicard, Length: 17 mm, Width: 8 mm, Colour: White

In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3321.7	MC GS 8/17 R t WH	4044211119058	200 PC
