

**3635.2**  
**ZS/H0/ZTR**  
**ZS/H0/ZTR**

---



Fuse plug, Colour: Yellow

## Business data

---

Product description	Fuse plug
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	6.34
Weight per piece (including packaging)	6.55
Unit of weight	G
Customs number	85369010
Country of origin	DE

## 3635.2 ZS/H0/ZTR ZS/H0/ZTR

### Technical Data

---

#### Ratings

---

Rated voltage (determined by the illuminated display and fuse being used)	400 V
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

#### Connection data

---

Connection principle	Plug in
----------------------	---------

#### Materials

---

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

## 3635.2 ZS/H0/ZTR ZS/H0/ZTR

### Technical Data

---

#### Further technical data

---

Fuse size	5 x 20 mm
Voltage illuminated display	500 V
Power loss in singular arrangement - overload and short-circuit protection, max.	2,5 / 6,4 W / A
Power loss in compound arrangement - overload and short-circuit protection, max.	1,6 / 6,4 W / A
Power loss in singular arrangement - only short-circuit protection, max.	5 / 6,3 W / A
Power loss in compound arrangement - only short-circuit protection, max.	2,5 / 6,4 W / A

## 3635.2 ZS/H0/ZTR ZS/H0/ZTR

### Approvals

---

#### CSA approval

---

CSA approval	C22.2 No 158
CSA approval granted	✓
CSA Usegroup B: rated voltage	300 V
CSA Usegroup B: rated current	10 A
CSA Usegroup C: rated voltage	300 V
CSA Usegroup C: rated current	10 A

#### CSAus approval

---

CSAus approval	UL 1059
CSAus approval granted	✓
CSAus Usegroup B: rated voltage	300 V
CSAus Usegroup B: rated current	10 A
CSAus Usegroup C: rated voltage	300 V
CSAus Usegroup C: rated current	10 A

3635.2  
ZS/H0/ZTR  
ZS/H0/ZTR

Media

---

