

3661.2

ZSLS 2,5/1A/2S GNYE

ZSLS 2,5/1A/2S GNYE



Protective earth terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Green-yellow

## Business data

Product description	Protective earth terminal
Packaging unit	100
Quantity unit	PC
Weight per piece (not including packaging)	11
Weight per piece (including packaging)	12
Unit of weight	G
Customs number	85369010
Country of origin	DE

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Technical Data

---

### Dimensions

---

Length	72.5 mm
Width	5.1 mm
Height	38.5 mm
Height TS 35/7.5	39.5 mm
Pitch	5 mm

### Ratings

---

Rated cross-section	2.5 mm <sup>2</sup>
Overvoltage category	III
Contamination degree	3

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Technical Data

---

### Connection data

---

Connection principle	Tension-spring connection
Connection position	Top
Connections	3
Number of terminals per level	3
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.5 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded, min.	0.5 mm <sup>2</sup>
Wire cross-section stranded, max.	4 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Wire cross-section AWG, min.	20
Wire cross-section AWG, max.	12
Stripping length	10 mm

### Materials

---

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Technical Data

---

### Materials

---

Working temperature, max.	120 °C
---------------------------	--------

---

### Further technical data

---

Mounting type	Mounting rail TS 35/7,5
---------------	-------------------------

---

Gauge plug acc. to EN 60 947-1	A3
--------------------------------	----

---

Number of cross-connection channels	1
-------------------------------------	---

---

End plate required	✓
--------------------	---

---

Number of test pick-off options	1
---------------------------------	---

---

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Approvals

---

### Standards and regulations

---

EAC approval	TR ZU 004/2011
--------------	----------------

EAC approval granted	✓
----------------------	---

### CSA approval

---

CSA approval	C22.2 No 158
--------------	--------------

CSA approval granted	✓
----------------------	---

CSA wire cross-section AWG, min.	20
----------------------------------	----

CSA wire cross-section AWG, max.	12
----------------------------------	----

CSA stripping length	10 mm
----------------------	-------

### CSAus approval

---

CSAus approval	UL 1059
----------------	---------

CSAus approval granted	✓
------------------------	---

CSAus wire cross-section AWG, min.	20
------------------------------------	----

CSAus wire cross-section AWG, max.	12
------------------------------------	----

CSAus stripping length	10 mm
------------------------	-------

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Approvals

---

### cUL Recognized

---

cUL Recognized	C22.2 No 158
cUL Recognized	✓
cUL wire cross-section single-core (rigid) AWG, min.	20
cUL wire cross-section single-core (rigid) AWG, max.	12
cUL wire cross-section stranded AWG, min.	20
cUL wire cross-section stranded AWG, max.	12
cUL wire material	Cu

### KEMA KEUR approval

---

KEMA KEUR approval	EN 60947-7-2
KEMA KEUR approval granted	✓
KEMA wire cross-section single core (rigid), min.	0.5 mm <sup>2</sup>
KEMA wire cross-section single-core (rigid), max.	4 mm <sup>2</sup>
KEMA wire cross-section stranded, min.	0.5 mm <sup>2</sup>
KEMA wire cross-section stranded, max.	4 mm <sup>2</sup>

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Approvals

---

### UL Recognized

UL Recognized	UL 1059
UL Recognized granted	✓
UL wire cross-section single-core (rigid) AWG, min.	20
UL wire cross-section single-core (rigid) AWG, max.	12
UL wire cross-section stranded AWG, min.	20
UL wire cross-section stranded AWG, max.	12
UL wire material	Cu
UL factory wiring	✓
UL field wiring	✓


3661.2

ZSLS 2,5/1A/2S GNYE

ZSLS 2,5/1A/2S GNYE

## Media

---



EAC





**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Accessories

---

### End plate

---



End plate, Width: 1.5 mm, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3681.2	ZAPS 2,5/1A/2S	4044211177591	50 PC

---

### Actuating tool

---



Actuating tool, No. of poles: 1, Colour: Black

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3808.0	BWMA 1 (0,5 x 3,5 mm)	4044211078850	1 PC

---

**3661.2**

**ZSLS 2,5/1A/2S GNYE**


**ZSLS 2,5/1A/2S GNYE**

## Accessories

---

### Coding

---



Coding, Colour: Orange

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3689.3	ZST-C	4044211177805	50 PC

---

### End bracket

---



End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 5 mm, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3811.2	ZES 35/2	4044211080600	50 PC

---

3661.2

ZSLS 2,5/1A/2S GNYE

ZSLS 2,5/1A/2S GNYE

## Accessories

---

### Test adapter

---




Test adapter, Pitch size: 5.1 mm, Colour: Beige

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3740.2	ZTA 2,5	4044211060497	10 PC

### Quick-marking

---



Terminal marker / Pocket Maxicard, Length: 5 mm,  
Width: 5 mm, Colour: White

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
4600.7	PMC SB 5/50 WH	4044211088903	500 PC

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Accessories

---

### Mechanical latch

---



Locking mechanism, Colour: Orange

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3687.3	ZST-V	4044211177911	50 PC

---



Locking mechanism, Colour: Orange

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3690.3	ZST-V-I	4044211185244	50 PC

---

**3661.2**

**ZSLS 2,5/1A/2S GNYE**

**ZSLS 2,5/1A/2S GNYE**

## Accessories

---

### Fourfold-cover

---



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

---

### In general

Order number	Article designation	GTIN (EAN)	Packaging unit
3706.0	ZAD 2,5/4/B	4044211060244	20 PC

---