


3711.5

ZQI 2,5/3 BU

ZQI 2,5/3 BU



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.2 mm, Rated cross-section: 2.5 mm<sup>2</sup>, Colour: Blue

## Business data

Product description	Insulated cross-connector
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	1.68
Weight per piece (including packaging)	1.7
Unit of weight	G
Customs number	85389099
Country of origin	DE

**3711.5**

**ZQI 2,5/3 BU**

**ZQI 2,5/3 BU**

## Technical Data

---

### Dimensions

---

Length	4.5 mm
Width	14.2 mm
Pitch size	5 mm

### Ratings

---

Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	24 A
Rated cross-section	2.5 mm <sup>2</sup>
Contamination degree	3

### Connection data

---

No. of poles	3
--------------	---

**3711.5**

**ZQI 2,5/3 BU**

**ZQI 2,5/3 BU**

## Technical Data

---

### Materials

---

Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

---

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	3