


3724.4

ZQI 4/6 BK

ZQI 4/6 BK



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 34.5 mm, Rated cross-section: 4 mm², Colour: Black

Business data

| | |
|--|---------------------------|
| Product description | Insulated cross-connector |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 4.3 |
| Weight per piece (including packaging) | 4.38 |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |

3724.4
ZQI 4/6 BK
ZQI 4/6 BK

Technical Data

Dimensions

| | |
|------------|---------|
| Length | 4.5 mm |
| Width | 34.5 mm |
| Pitch size | 6 mm |

Ratings

| | |
|---------------------------------|-------------------|
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 800 V |
| Rated current | 32 A |
| Rated cross-section | 4 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|--------------|---|
| No. of poles | 6 |
|--------------|---|

3724.4
ZQI 4/6 BK
ZQI 4/6 BK

Technical Data

Materials

| | |
|---------------------------|---------------|
| Material | Copper alloy |
| Surface | Tin-plated |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 6 |