

3724.5

ZQI 4/6 BU

ZQI 4/6 BU



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 34.5 mm, Rated cross-section: 4 mm<sup>2</sup>, Colour: Blue

## Business data

Product description	Insulated cross-connector
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	4.3
Weight per piece (including packaging)	4.38
Unit of weight	G
Customs number	85389099
Country of origin	DE

**3724.5**  
**ZQI 4/6 BU**  
**ZQI 4/6 BU**

## Technical Data

---

### Dimensions

---

Length	4.5 mm
Width	34.5 mm
Pitch size	6 mm

### Ratings

---

Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	32 A
Rated cross-section	4 mm <sup>2</sup>
Contamination degree	3

### Connection data

---

No. of poles	6
--------------	---

**3724.5**  
**ZQI 4/6 BU**  
**ZQI 4/6 BU**

## Technical Data

---

### Materials

---

Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

---

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	6