


3726.4

ZQI 4/8 BK

ZQI 4/8 BK



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 46.7 mm, Rated cross-section: 4 mm², Colour: Black

Business data

Product description	Insulated cross-connector
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.83
Weight per piece (including packaging)	5.92
Unit of weight	G
Customs number	85389099
Country of origin	DE

3726.4
ZQI 4/8 BK
ZQI 4/8 BK

Technical Data

Dimensions

Length	4.5 mm
Width	46.7 mm
Pitch size	6 mm

Ratings

Voltage with partition, max.	800 V
Voltage without partition, max.	800 V
Rated current	32 A
Rated cross-section	4 mm ²
Contamination degree	3

Connection data

No. of poles	8
--------------	---

3726.4

ZQI 4/8 BK

ZQI 4/8 BK

Technical Data

Materials

Material	Copper alloy
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	8