


5703.2

DM 12

DM 12



Diode module, With 12 diodes, Individually switched, Diode type 1N 4007, Screw connection, Mounting type: Mounting rail TS 35

Business data

Product description	Diode module
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	105.1
Weight per piece (including packaging)	162.3
Unit of weight	G
Customs number	85411000
Country of origin	EEC

5703.2

DM 12

DM 12

Technical Data

Dimensions

Length	87 mm
Width	69 mm
Height TS 35/7.5	57 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	7 mm
Torque	0.6 Nm

Input data

Max. operating voltage AC/DC	250 V
Current load per channel, max.	1 A
Number of channels	12

Materials

Working temperature, min.	-20 °C
Working temperature, max.	50 °C

Further technical data

Diode © CONTA-CLIP Verbindungstechnik GmbH | Otto-Hahn-Str. 7 | D-33161 Hovelhor
Fon +49 (0) 52 57.98 33-0 | Fax +49 (0) 52 57.98 33-33 | E-Mail info@conta-clip.de | conta-clip.de

Diode on-state voltage Creation date 08.06.2020 11:43:40

Diode reverse voltage Subject to technical modifications
1000 V

Diode reverse current

5 μ A

5703.2

DM 12

DM 12

Technical Data

5703.2

DM 12

DM 12

Approvals

Standards and regulations

Standards / specifications

DIN VDE 0110 / EN 50178

5703.2

DM 12

DM 12

Media

