

5714.2
SM 6-E
SM 6-E



Fuse module, 6 fuse cartridges for 5x20 micro-fuses, Individually switched, Screw connection, Mounting type: Mounting rail TS 35

Business data

Product description	Fuse modules
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	103.8
Weight per piece (including packaging)	131.55
Unit of weight	G
Customs number	85363010
Country of origin	EEC

5714.2
SM 6-E
SM 6-E

Technical Data

Dimensions

Length	87 mm
Width	47 mm
Height TS 35/7.5	77 mm

Ratings

Current load, max.	6,3 A
Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	7 mm

5714.2
SM 6-E
SM 6-E

Technical Data

Connection data

Torque	0.6 Nm
--------	--------

Input data

Max. operating voltage AC/DC	250 V
------------------------------	-------

Current load per channel, max.	4 A
--------------------------------	-----

Number of channels	6
--------------------	---

Materials

Working temperature, min.	-20 °C
---------------------------	--------

Working temperature, max.	50 °C
---------------------------	-------

Further technical data

Fuse size	5x20 mm
-----------	---------

5714.2

SM 6-E

SM 6-E

Approvals

Standards and regulations

Standards / specifications

DIN VDE 0110 / EN 50178
