## TOP VIEW




## SIDE VIEW




| Specifications | | |
|---|---|---|
| **Description** | **Value** | **Unit** |
| Resonant Frequency | 4,000 | (Hz) |
| Resonant Impedance (Max) | 500 | (Ohm) |
| Max Input Voltage | 20 | (V) |
| Capacitance | 20,000 | (pF) |
| Plate Material | Stainless Steel | |
| Operating Temperature | -20 ~ +60 | °C |
| Storage Temperature | -20 ~ +70 | °C |
| | | |
| | | |
| | | |
| | | |
| | | |

**Notes**

1) All dimensions are in mm unless otherwise noted
2) All parts meet RoHS

DB UNLIMITED

**Piezo Bender**

| Revision History | | | | | |
|---|---|---|---|---|---|
| **Version** | **Description** | | **Date** | **Approved** | |
| 1 | Released from Engineering | | 10/21/2013 | J.S | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| **Drawn by** | **Date** | **Checked by** | **Date** | **Approved by** | **Date** |
| A.B. | 10/21/2013 | C.E. | 10/21/2013 | J.S | 10/21/2013 |

**P27040-1**

sales@dbunlimitedco.com | www.dbunlimitedco.com
©2013, DB Unlimited