


TOP VIEW



SIDE VIEW



BOTTOM VIEW



| S | Specifications | | - Notes | | Revision History | | | | | |
|-----------------------|----------------|-------|-----------------------------|-----------------|---------------------------|------------|-------------|------------|-------------|----------|
| Description | Value | Unit | | | Version | | Description | | | Approved |
| Shape | Round | | 1) All dimensions are in mm | 1 | Released from Engineering | | | 2/5/2014 | J.S | |
| Resonant Frequency | 600 | (Hz) | 2) All parts meet RoHS | | | | | | | |
| Frequency Range | 600 ~ 20,000 | (Hz) | | | | | | | | |
| SPL @ 10cm | 90 | (dBA) | | | | | | | | |
| Impedance | 8 | (Ohm) | | | | | | | | |
| Cone Material | Mylar | | | | | | | | | |
| Nominal Power | 1 | (W) | | | | | | | | |
| Max Power | 1.5 | (W) | | | | | | | | |
| Mount Type | Flush Mount | | | | Drawn by | Date | Checked by | Date | Approved by | Date |
| Operating Temperature | - 20 ~ + 60 | °C | | | G.W. | 10/31/2013 | C.E. | 10/21/2013 | J.S | 2/5/2014 |
| Storage Temperature | - 20 ~ + 60 | °C | Dynamic Speaker | | | SM400608-1 | | | | |
| Weight | 9.2 | (g) | DB UNLIMITED | Dynamic Speaker | | 31400000-1 | | | | |