

Marine & Offshore Division

Certificate number: 23317/A2 BV

File number: ACE14/917/1 Product code: 2601D

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to

ABB France - Activite Raccordement

CHASSIEU CEDEX - FRANCE

for the type of product

TERMINAL BLOCKS (LOW VOLTAGE)

SCREW CLAMP TERMINAL BLOCKS SNK Series

Requirements:

Bureau Veritas Rules for the Classification of Steel Ships, IEC 60947-7-1 (2009), IEC 60947-7-2 (2009), IEC 60947-7-3 (2009)

This certificate is issued to attest that BUREAU VERITAS did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 18 Feb 2016

For BUREAU VERITAS,

At BV LYON, on 05 Feb 2015, Jean-Marc Cabuzel





This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with BUREAU VERITAS. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of BUREAU VERITAS Marine & Offshore Division available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against BUREAU VERITAS for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

Certificate number: 23317/A2 BV

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

SCREW CLAMP TERMINAL BLOCKS - SNK Series (including accessories)

| | RATED | RATED | RATED | Remarks |
|---------------|-------------|---------------|-------------|--|
| TYPES | VOLTAGE | CROSS-SECTION | CURRENT | |
| | (V) | (mm²) | A | |
| ZS4 | 1000 | 4 | 32 | Feed-Through |
| ZDS4-22 | 800 | 4 | 29 | Pluggable feed-through with 4 connections (2 |
| | | | | fixed and 2 plugs) |
| ZDS4-22-R1 | 800 | 4 | 29 | Pluggable feed-through with 4 connections (2 |
| | | | | fixed and 2 plugs) |
| ZS4-PE | - | 4 | = | Ground |
| ZS4-D1 | 800 | 4 | 29 | Double deck with 1 Feed-Through circuit |
| ZS4-D2 | 800 | 4 | 29 | Double deck with 2 Feed-Through circuits |
| ZS4-S | 400 | 4 | 25 | Disconnect with blade |
| ZS4-S-R1 | 400 | 4 | 26 | Disconnect with blade |
| ZS4-S-R2 | 400 | 2.5 | 18 | Disconnect with lever |
| ZS4-S-R3 | 500 | 2.5 | 18 | Disconnect with lever |
| ZS4-S-T2-R1 | 400 | 4 | 26 | Disconnect with blade + Test Socket Screws |
| ZS4-S-T2.3-R1 | 400 | 4 | 26 | Disconnect with blade + Test Socket Screws |
| ZS4-SF | 250 | 4 | 6.3 | 5x20 fuses |
| ZS4-SF-T2 | 250 | 4 | 6.3 | 5x20 fuses + Test Socket Screws |
| ZS4-SF-R1 | 250 (1) | 4 | 6.3 | 5x20 fuses + blown fuse Indicator |
| ZS4-SF-R2 | 250 (1) | 4 | 6.3 | 5x20 fuses + blown fuse Indicator + Test |
| | | | | Socket Screws |
| ZS4-SF-R3 | 250 | 4 | 6.3 | 5x20 fuses + blown fuse Indicator |
| ZS4-SF-R4 | 250 | 4 | 6.3 | 5x20 fuses + blown fuse Indicator+ Test |
| | | | | Socket Screws |
| ZS4-R1 | 800 | 2.5 | 24 | Feed-Through |
| ZS4-SF1 | 250 | 4 | 6.3 | 5x20 & 5x25 fuses |
| ZS4-SF1-T2 | 250 | 4 | 6.3 | 5x20 & 5x25 fuses + Test Socket Screws |
| ZS4-SF1-R1 | 250 (1) | 4 | 6.3 | 5x20 & 5x25 fuses + blown fuse Indicator |
| ZS4-SF1-R2 | 250 (1) | 4 | 6.3 | 5x20 & 5x25 fuses + blown fuse Indicator+ |
| 734 SE4 B2 | 250 | | | Test Socket Screws |
| ZS4-SF1-R3 | 250 | 4 | 6.3 | 5x20 & 5x25 fuses + blown fuse Indicator |
| ZS4-SF1-R4 | 250 | 4 | 6.3 | 5x20 & 5x25 fuses + blown fuse Indicator + |
| 704 00 | 000 | 4 | 22 | Test Socket Screws |
| ZS4-R2 | 800 | 4 | 32 | Feed-through |
| ZS4-PE-R2 | - | 4 | - | Ground |
| ZS4-D2-S | 630 | 4 | 25/29(3) | Double deck with 1 disconnect circuit and 1 feed-through circuit |
| ZS4-D2-S-T2 | 630 | 4 | 25/29(3) | Double deck with 1 disconnect circuit with test |
| | | | | socket screws and 1 feed-through circuit |
| ZS4-D2-SF1 | 800 | 4 | 6.3/25(4) | Double deck with 1 fuse circuit and 1 feed-through circuit |
| ZS4-D2-SF1-R1 | 800(1) | 4 | 6.3/25(4) | Double deck with 1 fuse circuit with blown fuse indicator and 1 feed-through circuit |
| ZS4-D2-SF1-R3 | 800(2) | 4 | 6.3/25(4) | Double deck with 1 fuse circuit with blown |
| | | · | 310, 20 (1) | fuse indicator and 1 feed-through circuit |
| ZS4-T3 | 800 | 4 | 32 | Triple deck with 3 feed-through circuits |
| ZS4-T3-R1 | 800 | 4 | 32 | Triple deck with 3 feed-through circuits |
| ZS6 | 1000 | 6 | 41 | Feed-Through |
| ZS6-PE | - | 6 | - | Ground |
| ZS6-D1 | 800 | 6 | 40 | Double deck with 1 Feed-Through circuit |
| ZS6-D1-PE | - | 6 | - | Double deck with 1 ground circuit |
| ZS6-D2 | 800 | 6 | 40 | Double deck with 2 Feed-Through circuits |
| ZS6-D2-PE | 800 | 6 | 41 | Double deck with 1 feed-through circuit and 1 |
| | 000 | | | ground circuit |
| ZS6-S | 500 | 4 | 25 | Disconnected with blade |
| 250-5 | 500 | 7 | 23 | Disconnected with blade |

Certificate number: 23317/A2 BV

| ZS6-3S | 800 | 4 | 32 | Feed-through with 3 connections |
|-------------|--------|----|-----|--|
| ZS6-3S-PE | - | 4 | - | Ground with 3 connections |
| ZS6-4S | 800 | 4 | 32 | Feed-through with 4 connections |
| ZS6-4S-PE | = | 4 | = | Ground with 4 connections |
| ZS6-S-4S-T2 | 500 | 4 | 27 | Disconnect with blade - with test socket |
| | | | | screws |
| ZS10 | 1000 | 10 | 57 | Feed-Through |
| ZS10-S | 630 | 4 | 25 | Disconnected with blade |
| ZS10-ST | 630 | 10 | 50 | Test disconnect with sliding link |
| ZS10-ST-1 | 630 | 10 | 50 | Test disconnect with sliding link for potential transformer circuits |
| ZS10-ST-T4 | 630 | 10 | 50 | Test disconnect with sliding link for current |
| | | | | transformer circuits |
| ZS10-SF | 630 | 10 | 10 | For 6.3x32 fuses |
| ZS10-R1 | 630 | 10 | 57 | Feed-through |
| ZS10-SF-R1 | 630(1) | 10 | 10 | For 6.3x32 fuses - with blown fuse indicator |
| ZS10-SF-R3 | 630(2) | 10 | 10 | For 6.3x32 fuses - with blown fuse indicator |
| ZS10-S-R2 | 630 | 4 | 25 | Disconnect with lever |
| ZS10-PE | - | 10 | - | Ground |
| ZS10-PE-R1 | - | 10 | - | Ground |
| ZS16 | 1000 | 16 | 76 | Feed-Through |
| ZS16-PE | - | 16 | - | Ground |
| ZS25 | 1000 | 16 | 76 | Feed-Through |
| ZS25-PE | - | 16 | - | Ground |
| ZS35 | 1000 | 35 | 125 | Feed-Through |
| ZS35-PE | - | 35 | - | Ground |
| ZS50 | 1000 | 50 | 150 | Feed-through |
| ZS50-PE | - | 50 | - | Ground |
| ZS70 | 1000 | 70 | 192 | Feed-Through |
| ZS70-PE | - | 70 | - | Ground |
| ZS95 | 1000 | 95 | 232 | Feed-Through |
| ZS95-PE | - | 95 | - | Ground |
| CDS4 | 800 | 4 | 29 | Female plug |
| CDS4-R1 | 800 | 4 | 29 | Female plug |
| CDS4-E | 800 | 4 | 29 | Female plug without outer nubs |

- (1): Operating voltage limited to 110V due to fuse indicator circuit, rated for 24-110V.
- (2): Operating voltage limited to 250V due to fuse indicator circuit rated for 115-250V
- (3): Disconnect circuit / feed-through circuit.
- (4): Fuse circuit / feed-through circuit.

2. DOCUMENTS AND DRAWINGS:

As per drawings Terminals Assembly, filed under BV ACE 14/917/01. SNK Series Data sheets

3. TEST REPORTS:

As per IEC CB Scheme test certificates FR 594321A to K, FR 594321B/A1, FR 599000 A to C, FR 602675, FR578472/M1, FR, 602677, FR578475/M1, FR578496/M1 issued by LCIE and SE-61023, SE-61024 issued by Intertek Semko AB. Environmental tests at ABB Laboratory: 20100605 dated 05/11/2010, 20070864-M1 dated 27/11/2007, 20071023-M1 dated 26/12/2007, 20071025-M1 dated 13/03/2008, 20071146-M1 dated 28/04/2008, 20071147-M1 dated 27/04/2009, 20071148-M1 dated 11/05/2009, 20071149-M1 dated 25/02/2010, 20071150-M1 dated 26/02/2010, 20080167-M2 dated 03/12/2009, 20080168-M1 dated 15/12/2009, 20080205-M1 dated 14/03/2008, 20080252-M1 dated 21/04/2009, 20080253-M1 dated 12/05/2009, 20080254-M1 dated 09/06/2009, 20080255-M1 dated 09/06/2009, 20080526-M1 dated 10/11/2009, 20080774-M1 dated 10/11/2009, 20080915-M1 dated 10/11/2009, 20090178-M dated 14/04/2009, 20090179-M dated 14/04/2009, 20090180-M dated 14/04/2009, 20090181-M dated 14/04/2009, 20090259-M1 dated 10/11/2009, 20090260-M1 dated 06/11/2009.

IECEE CB Scheme Certificate N°FR663430, dated 12.Dec.2014.

ABB France:

Test Report $N^{\circ}20110412\text{-M}$, dated 28.Jan.2013.

Test Report N°20140343, dated 1. Oct.2014.

Certificate number: 23317/A2 BV

4. APPLICATION / LIMITATION:

- 4.1 BV Rules for the Classification of Steel Ships, BV Rules for the Classification of Offshore Units and IEC 60092 series.
- 4.2 Approval also valid for ships to be granted with the notations: AUT-UMS, AUT-CCS, AUT-PORT and AUT-IMS.

5. PRODUCTION SURVEY REQUIREMENTS:

- 5.1 The terminal blocks are to be supplied by **ABB France** in accordance with the type described in this certificate.
- 5.2 This type of product is within the category DBV of Bureau Veritas Rule Note NR320.

6. MARKING OF PRODUCT:

- According to IEC 60947 specification.
- Trade Mark ABB.

7. OTHERS:

- 7.1 The approval is given with the understanding that the Society reserves the right the require check tests to be carried out on the units at any time, and that **ABB France**, **Chassieu France**, will accept full responsibility for informing shipbuilders, shipowners or their sub-contractors of the proper methods of use and general maintenance of the units and the conditions of this approval.
- 7.2 This certificate supersedes the Type Approval Certificate N° 23317/A1 BV issued on 18.07.2013. by the Society.

*** END OF CERTIFICATE ***