

CS Circuit Separators

Terminal Blocks Accessories

Catalogue Page 1SNK 160 018 S0201



RoHS
RoHS

0 mm 0 in spacing

Mounting Instructions

Features and Benefits

- The CS circuit separator avoids the derating of terminal blocks when cut jumper bars JB are used,
- Compatible with feed-through terminal blocks up to 16 mm² 4 AWG,
- Without spacing loss.

Ordering Details

Description	Color	Type	Order Code	Pack ^(incl) pieces	Weight (1 pce) g
0 mm 0 in spacing	Dark Grey ■	CS	1SNK 900 101 R0000	20	0.20

Main Technical Data

Material Specifications	Insulating material	Polyamide		
Flammability	V0			
NF F 16 101	I2F2			
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F	
Storage	-55 +110 °C -67 +230 F			
Installing	-5 +40 °C -23 +104 F			

CS-R1 Circuit Separators

Terminal Blocks Accessories

Catalogue Page 1SNK 160 018 S0201



RoHS
RoHS

3 mm 0.118 in spacing

Mounting Instructions

Features and Benefits

- Ease the visual identification of the several circuits within your terminal block assemblies,
- Compatible with feed-through terminal blocks up to 35 mm² 0 AWG,
- Intermediate cover holder for CO protective cover,
- Mounting on DIN3-TH35 rail.

Ordering Details

Description	Color	Type	Order Code	Pack ^(incl) pieces	Weight (1 pce) g
3 mm 0.118 in spacing	Dark Grey ■	CS-R1	1SNK 900 103 R0000	20	5.20

Main Technical Data

Material Specifications	Insulating material	Polyamide		
Flammability	V0			
NF F 16 101	I2F2			
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F	
Storage	-55 +110 °C -67 +230 F			
Installing	-5 +40 °C -23 +104 F			

Accessories

Description	Color	Type	Order Code	Pack ^(incl) pieces	Weight (1 pce) g
Blank card	White □	MC512	1SNK 140 000 R0000	22	9.00
		MC512PA	1SNK 149 999 R0000	20	10.00
Universal wire markers holder	Grey ■	UMH	1SNK 900 611 R0000	10	0.20
Self adhesive strip	White □	SAT5	1SNK 900 614 R0000	5	6.00

Some accessories may modify the terminal block's ratings. See complete information in "Technical Datasheet".

All the technical data for UL/CSA standard and dimensions in inches are in italic.