



PART NO.	"B"	MAX. BUNDLE DIA. "C" LOCKED	BOARD THICKNESS RANGE
SLCSE-250	.57 (14.5)	.22 (5.6)	1/32-5/64 (0.8-2.0)
SLCSE-370	.71 (18.0)	.35 (8.9)	
SLCSE-500	.83 (21.0)	.47 (12.0)	
SLCSE-750	1.08 (27.5)	.73 (18.4)	5/64-5/32 (2.0-4.0)
SLCSE2-250	.57 (14.5)	.22 (5.6)	
SLCSE2-370	.71 (18.0)	.35 (8.9)	
SLCSE2-500	.83 (21.0)	.47 (12.0)	
SLCSE2-750	1.08 (27.5)	.73 (18.4)	

PART NO. CODE  
 SLCSE - 500 - 8 - 01  
 |           |           |           |  
 PART#    SIZE    "A"    MAT'L

SUFFIX	"A" ±.015(0.4)
-3	3/16(4.8)
-4	1/4(6.4)
-6	3/8(9.5)
-8	1/2(12.7)
-10	5/8(15.9)
-12	3/4(19.1)
-14	7/8(22.2)
-16	1.0(25.4)

NOTES:

- MAT'L: NYLON 66 (RMS-01)
- COLOR: NATURAL
- FLAME RETARDANT NYLON (RMS-19), AVAILABLE BY SPECIAL ORDER.

TITLE: STANDOFF LOCK CLIP SERIES				⊕	▭	DWG IN IN (MM)	QR
TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°	FILE # SLCSE	DWN: J.B.	APP:	FINAL			
	MAT'L: SEE NOTES	DT: 02-13-96	DT:	PART #		PRINT TYPE	
	RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060		SEE CHART		CA	

A	CHANGED FILE NUMBER	SM 05.31.01
REV	DESCRIPTION	ENGR DATE