

1363 Capital Drive Fond du Lac, WI 54937

Main: (920) 922-6490 Fax: (920) 922-6750

Email: info@fedcobatteries.com www.FedcoBatteries.com

PRODUCT DATA SHEET Lithium-ion Rechargeable Battery Pack

ENERGY+® Model No. DR202E

PACK SPECIFICATIONS:

Voltage (Nominal): 10.8 VDC Capacity (Nominal): 9150 mAHr

Energy: 98.8 Watt-Hours (Whr)

Pack Configuration: 3 in series, 3 in parallel. (3S3P)

Cycle Life: 500 Cycles PCM: BMS with SMBus

Connector: 5 Position Molded Into Case

Weight: 1.05

OPERATING SPECIFICATIONS:

Operating Voltage: 8.4 VDC to 12.6 VDC

Discharge Current: 5000mA continuous, 5500mA max


Charge Voltage: 12.6 VDC
Charge Current: 2500mA max
Temperature Range in °C (Discharge): 0 to +60
Temperature Range in °C (Charge): 0 to +45

STORAGE SPECIFICATIONS:

Temperature Range °C (Storage) -10 to +50 Relative Humidity Range: 45% to 85%

REGULATORY COMPLIANCE:

UN38.3, UL2054, IEC:62133



REV: A DATE: 05/15/2019

