

REV

PART NO

GENERAL SPECIFICATIONS:

RATING: 2.5A / 250V AC

H05VV-F, 3 x 0.75 mm² CABLE TYPE / SIZE:

70° C TEMPERATURE RATING:

BLUE / BROWN / GREEN-YELLOW CONDUCTOR COLORS:

BI ACK CABLE JACKET COLOR: OVERALL LENGTH (L): 2050 ± 50 mm CABLE OUTER DIAMETER: 6.7 ± 0.1 mm

END 'A' TERMINATION: INDIA/SOUTH AFRICAN TYPE PLUG (16A), 2 POLE + GROUND

RIGHT ANGLE STYLE (BS456/IA16A3/SABS164)

END 'B' TERMINATION: IEC 320 / C5 FEMALE

APPROVALS PLUG: SABS

APPROVALS CABLE: VDE, N, S, D, FI, KEMA, SEV, CEBEC, OVE, SAA, IMMEQ

APPROVALS CONNECTOR: **ENEC-10-VDE**

NOTES:

Contents of this document

prior notice

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBERS.



2. CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBERS.



Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair are subject to change without occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.


Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

DASH

PACKING:

HANKING

 $L = 200 \pm 20 \text{ mm}$



RELEASED By N.Frost at 10:51 am, Sep 22, 2016

NOTES

	NO.	Truct No	KLV.		BESCRI HOW	NOTES
				TA	ABULATION BLOCK	
			TOLERA DECIMALS .xx +/- 0.1 .xxx +/005	ANCES: ANGULAR +/- 1°	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Nor Tel. 201-784-1000	
INIT.BY: BS DATE: MILLIMETERS ANGULAR 2.xx +/- 0.3				ANGULAR +/- 1°	DWG TITLE: INDIA / SOUTH AFRICAN DETACHABLE	CORDSET
	DRAWN: N	DATE: 08/11/10	FSCN No.: G, CC	SIZE A	MODEL: N / A	REV. C
	APRVD: HN	DATE: 08/11/10	SCALE: N	IONE	PART NO: 2084262M0712(R)	SHEET 1/1

DESCRIPTION