

GENERAL SPECIFICATIONS:

RATING: 10A / 250V AC

H05VV-F, $3 \times 1.5 \text{ mm}^2$ CABLE TYPE / SIZE:

TEMPERATURE RATING: 70° C

CONDUCTOR COLORS: BROWN / BLUE/ GREEN-YELLOW

CABLE JACKET COLOR: BLACK OVERALL LENGTH (L): 2550 ± 50 mm CABLE OUTER DIAMETER: $8.5 \pm 0.1 \text{ mm}$ END 'A' PLUG: CEE 7/7

END 'B': SEE TERMINATION TABLE

APPROVALS: VDE, N, D, FI, KEMA, OVE, CE, IMQ, S, USE, CEBEC

CONDUCTOR TERMINATION TABLE:

Wire	Color	ROJ ± 5 mm	RIJ±1 mm	Terminal
Ground	Green-Yeloow	127	5	STRIPPED
Neutral	Blue	127	5	STRIPPED
Line	Brown	127	5	STRIPPED

PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR

NOTES:

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

REVISION



PACKING:

BULK PACKED, BUNDLES OF 25. MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

		DASH NO.	PART NO	REV.		DESCRIPTION NOTES			
			TABULATION BLOCK						
				TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1* .xxx +/005		GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111			
Contents of this document are subject to change without occurs. End user should consult the applica-	Limitation of Use: Globtek product are not authorized for use as mission critical components in life support,	INIT.BY: EM	DATE: 03/13/09	MILLIMET .xx +/- 0 .xxx +/	.3 +/- 1°				
	product if unauthorized access and repair occurs. End user should consult the applica- ble UL,CSA or EN Standards for proper	hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	DRAWN: NF	DATE: 03/13/09	FSCN N G, CC	o.: SIZI	E REV.		
			APRVD: HM	DATE: 03/13/09	SCALE	: NONE	PART NO: 23144282M5001(R) SHEET 1/1		