

GENERAL SPECIFICATIONS:

RATING:	6A / 250V AC
CABLE TYPE / SIZE:	HO5RR-F, 3x1 mm ²
TEMPERATURE RATING:	70°C
CONDUCTOR COLORS:	BLUE / BROWN / GREEN-YELLOW
CABLE JACKET COLOR:	BLACK
OVERALL LENGTH:	3200 <u>+</u> 50 mm
END 'A' PLUG:	CEE 7/7 STRAIGHT
END 'B' :	SEE TERMINATION TABLE
APPROVALS PLUG:	VDE, N, S, D, FI, KEMA, CEBEC, OVE
APPROVALS CABLE:	<har></har>


CONDUCTOR TERMINATION TABLE:

PACKING:

BULK PACK MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

NOTES:

1. PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



2. CORD MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

Wire	Color	$ROJ \pm 5 mm$	$RIJ \pm 1 mm$	Terminal
Neutral	Blue	120	6	STRIPPED
Line	Brown	120	6	STRIPPED
Ground	Green/Yellow	120	6	STRIPPED

<HAR>



RoHS		DASH NO.	PART NO	REV.		DESCRIPTION	NOTES	
		TABULATION BLOCK						
		REV.		TOLER DECIMALS .xx +/- 0.1	ANCES: ANGULAR +/- 1°	GlobTek, Inc. 186 Veterans Dr. Nort		
		SHEET		.xxx +/005		www.globtek.com Tel. 201-784-1000 F	ax 201.784.0111	
	Foot Note: Globtek Inc. will not be liable for the safety and performance of these power Limitation of Use: Globtek product are not authorized for use as mission critical components in life support, h	INIT.BY: BS	DATE: 08/14/17	MILLIMETER .xx +/- 0.3 .xxx +/013	S ANGULAR +/- 1*	DWG TITLE: EUROPEAN NON-DETACHABLE CORDSE	Т	
are subject to change without	product if unauthorized access and repair occurs. End user should consult the applica-		DRAWN: NF	DATE: 08/14/17	FSCN No.: G, CC	SIZE A	MODEL: N / A	REV. A
	installation instruction.		APRVD: MK	DATE: 08/14/17	SCALE: 1	NONE	PART NO: 23144473M200	SHEET 1/1