


**PROPRIETARY INFORMATION:**  
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.


REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 22802, BS	04/16/12	HM
B	UPDATE CONDUCTORS COLOR AND HANKING SIZE, RFS.23517, BS	09/17/12	HM
C	UPDATE LENGTH TO 1800±50 ON THE DRAWING, RFS.26107, BS	10/30/15	HM
D	CORRECT CORDSET RATING FROM 15A/125VAC TO 7A/125VAC, RFS.26440, BS	09/06/16	HM



**GENERAL SPECIFICATIONS:**

RATING: 7A / 125V AC  
 CABLE TYPE / SIZE: HVCTF 3 x 0.75 mm<sup>2</sup>  
 TEMPERATURE RATING: 105° C  
 CONDUCTOR COLORS: BLACK / WHITE / GREEN-YELLOW  
 CABLE JACKET COLOR: BLACK  
 OVERALL LENGTH (L): 1800 ± 50 mm  
 CABLE OUTER DIAMETER: 7.0 ± 0.1 mm  
 END 'A' PLUG; JAPAN JIS 8303 / 3 PINS  
 END 'B' IEC 320 / C5  
 APPROVALS PLUG: MITI or PSE  
 APPROVALS CABLE: MITI or PSE  
 APPROVALS CONNECTOR: MITI or PSE

**PACKING:**  
 HANKING



**RELEASED**  
 By N.Frost at 4:30 pm, Sep 06, 2016

**NOTES:**

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



Foot Note:  
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:  
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
<b>TABULATION BLOCK</b>				
		<b>TOLERANCES:</b> DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005		<b>GlobTek, Inc.</b> www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
		MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013		
INIT.BY: BS	DATE: 04/16/12	<b>DWG TITLE:</b> JAPANESE DETACHABLE CORDSET, 3 x 0.75 mm <sup>2</sup>		
DRAWN: NF	DATE: 04/16/12	FSCN No.: G, CC	SIZE: A	REV. D
APRVD: HM	DATE: 04/16/12	SCALE: NONE	PART NO: 3003316F0712(R)	SHEET 1/1