
PROPRIETARY INFORMATION:


PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS.13283, EM	04/01/08	BS
В	UPDATE APPROVALS, RFS. 24324, EM	02/28/13	HM
С	REVISE TEMPERATURE RATING FROM 75°C TO 70°C, RFS. 25503, JN	04/29/14	HM









GENERAL SPECIFICATIONS:

RATING: 2.5A / 250V AC

CABLE TYPE / SIZE: HO3VVH2-F, 2 x 0.75 mm², 2 CONDUCTOR

TEMPERATURE RATING: 70°C **BLACK** CABLE JACKET COLOR: CONDICTORS COLOR: BLUE/ BRN OVERALL LENGTH (L): 2000 ± 50 mm CABLE OUTER DIAMETER: 3.5 x 5.7 ± 0.15 mm END 'A': BS1363 (FUSE 3A)


END 'B': IEC320 / C7

APPROVALS PLUG: BSI or ASTA or NEMKO; HK SAFETY MARK

APPROVALS CABLE: BSI or ASTA or NEMKO

APPROVALS CONNECTOR: VDE, ENEC

PACKING: HANKING



REV.

TOLERANCES:

.xx +/- 0.1

.xxx +/- .005

.xx +/- 0.3

xxx +/= 013

FSCN No.:

SCALE: NONE

G, CC

DECIMALS ANGULAR

SIZE

PART NO

DATE:

04/01/08

DATE:

04/01/08

DATE:

04/01/08



NOTES

SHEET 1/1

RELEASED

DESCRIPTION

By N.Frost at 9:39 am, Apr 29, 2014

NOTES:

1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS AND / OR FILE NUMBERS.











OR



DASH

INIT.BY: EM

DRAWN: NF

APRVD: HM

Globtek product are not authorized for use as mission critical components in life support,

hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

TABULATION BLOCK

GlobTek, Inc. www.globtek.com

186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111

MILLIMETERS ANGULAR DWG TITLE: BRITISH AND HONG KONG DETACHABLE CORDSET

REV. C

PART NO: 6104112M703A(R)

Contents of this document are subject to change without prior notice

Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction.