


PROPRIETARY INFORMATION:
 PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR
 USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY
 PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

| REVISION | | | |
|----------|---------------------------------|----------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| A | INITIAL RELEASE, RFS. 23376, EM | 08/21/12 | BS |
| | | | |




GENERAL SPECIFICATIONS:


RATING: 15A / 250V AC, 15A / 125V AC
 DUAL MARKED CABLE: H05VV-F 3x1.5 mm², 70°C, 16A/250V
 SJT 14X3, 105°C, 15A/300V
 CORDSET COLOR: BLACK
 OVERALL LENGTH: 2438±50 mm (8 ft)
 CABLE OUTER DIAMETER: 9.4 ± 0.2 mm
 END 'A' PLUG: IEC 320 / C19 (female)
 END 'B': IEC 320 / C20 (male)
 APPROVALS PLUG: UL, CSA or cUL, CE and VDE MINIMUM
 APPROVALS CABLE: UL, CSA or cUL, CE and VDE MINIMUM
 APPROVALS CONNECTOR: UL, CSA or cUL, CE and VDE MINIMUM

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).
2. CERTIFICATIONS: CE, ROHS



2. CABLE IS DUAL APPROVED FOR NORTH AMERICA AND EUROPE.

| DASH NO. | PART NO | REV. | DESCRIPTION | NOTES |
|-------------------------|----------------|--|-----------------------------------|---|
| TABULATION BLOCK | | | | |
| | | TOLERANCES: DECIMALS ANGULAR .xx +/- 0.1 +/- 1° .xxx +/- .005 | |  GlobTek, Inc. www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111 |
| | | MILLIMETERS ANGULAR .xx +/- 0.3 +/- 1° .xxx +/- .013 | | |
| INIT.BY: EM | DATE: 08/21/12 | DWG TITLE: INTERNATIONAL DETACHABLE JUMPER CORDSET C19/C20, LENGTH: 8 ft, COLOR: BLACK | | REV. A |
| DRAWN: NF | DATE: 08/21/12 | FSCN No.: G, CC | SIZE A | |
| APRVD: HM | DATE: 08/21/12 | SCALE: NONE | PART NO: 70335148F07032(R) | SHEET 1/1 |

Contents of this document are subject to change without prior notice

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.