

GENERAL SPECIFICATIONS:

RATING: 10A / 250V AC

CABLE TYPE / SIZE: SJT AWG 18X3 / H05VVF 3X1.0 mm²

TEMPERATURE RATING: 60° C

CONDUCTOR COLORS: BLUE / BROWN / GREEN-YELLOW

CABLE JACKET: BLACK COLOR, LOW LEAD PVC < 3000 ppm

OVERALL LENGTH (L): $5000 \pm 50 \text{ mm}$ CABLE OUTER DIAMETER: $8.3 \pm 0.2 \text{ mm}$ END 'A' PLUG; IEC 320 / C14 END 'B' IEC 320 / C13

APPROVALS PLUG: UL, CSA or cUL, VDE, N, S, D, FI, KEMA, SAA, UTE, CEBEC, OVE, IMQ, SEV

APPROVALS CABLE: UL, CSA or cUL, VDE, N, S, D, FI, KEMA, SAA, SEV, CEBEC, OVE, IMQ

APPROVALS CONNECTOR: UL, CSA or cUL, VDE, N, S, D, FI, BSI, KEMA, SEV, SAA, IMQ, UTE, CEBEC, OVE

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).






2.CABLE IS 3C/18 AWG/SJT AND 3C/1mm²/H05VV-F DUAL APPROVED FOR US AND EUROPE.

Contents of this document are subject to change without prior notice

Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL,CSA or EN Standards for proper installation instruction. Limitation of Use: Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

PACKING: HANKED







APPROVED

07/19/07

NO.	PART NO	REV.	DESCRIPTION			NOTES
TABULATION BLOCK						
		DEC .xx	+/- 0.1 +/005	NGULAR +/- 1*	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Nor Tel. 201-784-1000	
INIT.BY:	EM DATE: 07/19/07	.xx +	METERS A +/- 0.3 +/013	ANGULAR +/- 1°	DWG TITLE: INTERNATIONAL JUMPER CORDSET, 5 METERS	
DRAWN	: NF DATE: 07/19/07	FSCN G, CC		SIZE A		REV. A
APRVD:	HM DATE: 07/19/07	SCA	SCALE: NONE		PART NO: 7055005M0701(R)	SHEET 1/1