HellermannTyton

111-01266

Article Number: 111-01266

Solar Tie, 11.9" Long, 56lb Tensile Strength, PA11W, Black, 100/pkg



RoHS



Base Data

Local Order Number 111-01266

Type GL300

Color Black (BK)

Features and Benefits • Nylon 11 cable ties provide excellent resistance to UV, chemical and moisture sensitive environments.

· Inside serrations and smooth edges allow for a strong hold on cables and wire bundles without damaging them.

· Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton solar cable ties are made of specially formulated materials providing various levels of UV, chemical

and moisture resistance, making it ideal for outdoor use. The cable ties feature inside serrations providing a positive hold onto wire and cable bundles and smooth edges to prevent bundle damage. The head design guarantees high tensile strength, as well as a low insertion force. Tensioning tools are available to ensure consistent and safe

installation.

Short Description Solar Tie, 11.9" Long, 56lb Tensile Strength, PA11W, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 56 lbs

Minimum Tensile Strength (Metric) 250 N

Length L (Imperial) 11.9 "

Length L (Metric) 301.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.8 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 3.2 "

Bundle Diameter Max. (Metric) 80.0 mm

Thickness T (Metric) 1.5 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 5000

Material and Specifications

Material Polyamide 11, UV-resistant (PA11W)

Material Shortcut PA11W

Operating Temperature $-40^{\circ}\text{F to } +221^{\circ}\text{F } (-40^{\circ}\text{C to } +105^{\circ}\text{C})$

ROHS Compliant Yes

Certification/Specification Det Norske Veritas

© HellermannTyton 2015