


## Specification Sheet

Part Number: 151-01033



Connector Clip w/Oval Fir Tree, 0.6 - 3.0 mm Panel Thickness, 6.2–13.0mm Mounting Hole, PA66HIRHSUV, Black, 1000/ctn

**Article Number** 151-01033

**Type** CCOVAL6

**Color** Black (BK)

**Features & Benefits**

- Short low profile fir tree to avoid obstructions on opposite side of panel.
- Oval hole fir tree prevents rotation and provides easy insertion with high extraction in 4 common automotive oval hole sizes.
- Fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit into the hole.
- Connector clip designed to meet USCAR EWCAP -005-11 clip slot specifications.

**Quantity Per** carton

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Connector Clip w/Oval Fir Tree, 0.6 - 3.0 mm Panel Thickness, 6.2–13.0mm Mounting Hole, PA66HIRHSUV, Black, 1000/ctn

**Global Part Name** CCOVAL6-PA66HIRHSUV-BK

**Length L (Imperial)** 1.16

**Length L (Metric)** 29.34

**Fixation Method** Fir Tree for oval holes

**Width W (Imperial)** 0.69

**Width W (Metric)** 17.63

**Height H (Imperial)** 0.60

**Height H (Metric)** 15.2

**Panel Thickness Min(Imperial)** 0.02

**Panel Thickness Max(Imperial)** 0.12

**Panel Thickness Min (Metric)** 0.6

**Panel Thickness Max (Metric)** 3.0

<b>Mounting Hole Diameter D (Imperial)</b>	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47
<b>Mounting Hole Diameter D (Metric)</b>	6.5 x 13.0 mm 6.5 x 12.5 mm 6.2 x 12.2 mm 7.0 x 12.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.51
<b>Mounting Hole Diameter D Max (Metric)</b>	13.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)