

Specification Sheet

Part Number: 151-01296



Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHSUV, Black, 3000/carton

Article Number 151-01296

Type CC18

Color Black (BK)

Features & Benefits

- HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.
- Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.
- HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Connector Clip, Mounting Hole Dia. 9.0–17.0mm, PA66HIRHSUV, Black, 3000/carton

Global Part Name CC18-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 35

Minimum Tensile Strength (Metric) 155

Length L (Imperial) 1.19

Length L (Metric) 30.29

Fixation Method Fir Tree

Width W (Imperial) 0.80

Width W (Metric) 20.32

Height H (Imperial) 0.93

Height H (Metric) 23.57

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.37

Panel Thickness Min (Metric)	0.51
Panel Thickness Max (Metric)	9.5
Mounting Hole Diameter D (Imperial)	0.35 x 0.67
Mounting Hole Diameter D (Metric)	9.0 x 17.0 mm
Mounting Hole Diameter D Min (Imperial)	0.35
Mounting Hole Diameter D Max (Imperial)	0.67
Mounting Hole Diameter D Max (Metric)	17.0
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)