

Specification Sheet

Part Number: 151-01310



Dual FT6 Docking Clip, 12-15mm with 6.5mm Fir Tree, PA66HIRHSUV, Black, 2000/pkg

Article Number 151-01310

Type DUALFT6DOCK

Color Black (BK)

Features & Benefits

- Fir Tree demonstrates easy insertion with high extraction resistance in 6.5 +/- 0.4 mm hole.
- C-clip design allows for multiple uses, from hoses and tubes to harnesses and cables.

Quantity Per carton

Product Description

HellermannTyton connector clips for oval holes are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The fir tree locks into place when inserted into the hole palpably and ensures a secure fixing at all times. Dual routing clip provides a secure fit for two routings between 12 - 15 mm diameter.

Short Description	Dual FT6 Docking Clip, 12-15mm with 6.5mm Fir Tree, PA66HIRHSUV, Black, 2000/pkg
Global Part Name	DUALFT6DOCK-PA66HIRHSUV-BK
Length L (Imperial)	2.04
Length L (Metric)	51.8
Width W (Imperial)	0.66
Width W (Metric)	16.66
Height H (Imperial)	1.36
Height H (Metric)	34.63
Nominal Diameter (Metric)	15.5
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.24
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	6.5 mm

Mounting Hole Diameter D Max (Metric) 6.9

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

ROHS Complaint Yes

Package Quantity(Imperial) 2000

Package Quantity (Metric) 2000

Customs Number 3926909988

Weight (Metric) 6.53

Weight (Imperial) 14.39