

## Specification Sheet

Part Number: 151-02076



Connector Clip w/Arrowhead, 0.7 - 3.0mm Panel Thickness, 6.5 x 13.0mm Hole Diameter, PA66HIRHSUV, Black, 5000/box

**Article Number** 151-02076

**Type** CCIVSFT6.5x130

**Color** Black (BK)

**Features & Benefits**

- HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications.
- Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.
- HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

**Quantity Per** bag

<b>Product Description</b>	HellermannTyton connector clips, for oval holes, are mounted simply by pushing them onto the corresponding clip. The clips provide a wide range of mounting options with anti-rattle and anti-rotation features. The fir tree locks into place when inserted into the hole palpably and ensures a secure fixing at all times.
<b>Short Description</b>	Connector Clip w/Arrowhead, 0.7 - 3.0mm Panel Thickness, 6.5 x 13.0mm Hole Diameter, PA66HIRHSUV, Black, 5000/box
<b>Global Part Name</b>	CCIVSFT6.5x130-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.91
<b>Length L (Metric)</b>	23.0
<b>Fixation Method</b>	Arrowhead (Small Mount)
<b>Width W (Imperial)</b>	0.77
<b>Width W (Metric)</b>	19.6
<b>Height H (Imperial)</b>	0.57
<b>Height H (Metric)</b>	41.6
<b>Panel Thickness Min(Imperial)</b>	0.03
<b>Panel Thickness Max(Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.7
<b>Panel Thickness Max (Metric)</b>	3.0

**Mounting Hole Diameter D (Imperial)** 0.26 " x 0.52

**Mounting Hole Diameter D (Metric)** 6.5 x 13.0 mm

**Mounting Hole Diameter D Min (Imperial)** 0.26

**Mounting Hole Diameter D Max (Imperial)** 0.52

**Mounting Hole Diameter D Max (Metric)** 13.0

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +257°F (-40°C to +125°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988

**Weight (Metric)** 5.53

**Weight (Imperial)** 12.2