

## Specification Sheet

Part Number: 151-02437



**Article Number**

151-02437

**Type**

RCD180XM12X17SS

**Color**

Black (BK)

**Features & Benefits**

- One-piece ratchet closure design allows for easy installation during pre- or final assembly.
- Four sizes and multiple configurations handle a wide range of diameters and applications, reducing part inventory.
- Clamp interior is designed to guide and center bundle to reduce pinching.
- Easy release feature allows for quick adjustments and maintenance.
- Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.
- Soft material inserts are available for sensitive bundles.
- For pre-determined clamp pressure, a Tension Tab is available for use with our EVO Series hand tools.

**Quantity Per**

carton

|  |  |
|--|--|
| <b>Product Description</b>                 | The Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The one-piece adjustable clamp can be closed by hand to the desired diameter. The release feature provides easy and nondestructive removal of cables simply by using a flat-head screwdriver. This nondestructive release allows the clamp to be reused without removing or replacing any bolts or screws. |
| <b>Short Description</b>                   | Ratchet P-Clamp, 1.38"-2.01" Bundle Dia, 180° Long, .47X.66 Hole Dia, PA66HIRHSUV/SS304, Black, 140/ctn  |
| <b>Global Part Name</b>                    | RCD180XM12X17SS-PA66HIRHSUV/SS304-BK   |
| <b>Minimum Tensile Strength (Imperial)</b> | 100.0  |
| <b>Minimum Tensile Strength (Metric)</b>   | 445.0  |
| <b>Length L (Imperial)</b>                 | 7.69   |
| <b>Length L (Metric)</b>                   | 195.2  |
| <b>Fixation Method</b>                     | Screw Mounting   |
| <b>Variant</b>                             | Fixing clamp   |
| <b>Width W (Imperial)</b>                  | 1.37   |
| <b>Width W (Metric)</b>                    | 34.9   |
| <b>Bundle Diameter Min (Imperial)</b>      | 1.42   |
| <b>Bundle Diameter Min (Metric)</b>        | 36.0   |

|  |                |
|--|----------------|
| <b>Bundle Diameter Max (Imperial)</b>      | 2.0            |
| <b>Bundle Diameter Max (Metric)</b>        | 51.0           |
| <b>Mounting Hole Diameter D (Imperial)</b> | 0.47 " x 0.66  |
| <b>Mounting Hole Diameter D (Metric)</b>   | 12.0 x 17.0 mm |

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Stainless Steel (SS304)

**Material Shortcut** PA66HIRHSUV SS304

**UV Resistant (Yes/No)** Yes

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 140

**Package Quantity (Metric)** 140

**Customs Number** 3926909988

