

## Specification Sheet

Part Number: 151-02459



USCAR Conn Clip with Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn

**Article Number** 151-02459

**Type** CC11FTM6

**Color** Black (BK)

**Features & Benefits**

- Connector clip design to meet USCAR EWCAP-005-11 clip slot specifications.
- Meets installation and extraction requirements of SAE/USCAR-2.
- Versatile and robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 5mm hole and M6 threaded hole.

**Quantity Per** carton

<b>Product Description</b>	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
<b>Short Description</b>	USCAR Conn Clip with Fir Tree, 11mm, 5.0 mm Dia and M6 Threaded Hole, PA66HIRHSUV, Black, 5000/ctn
<b>Global Part Name</b>	CC11FTM6-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.98
<b>Length L (Metric)</b>	24.9
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.622
<b>Width W (Metric)</b>	15.8
<b>Height H (Imperial)</b>	0.814
<b>Height H (Metric)</b>	20.7
<b>Panel Thickness Min (Metric)</b>	1.3
<b>Panel Thickness Max (Metric)</b>	4.5
<b>Mounting Hole Diameter D Max (Metric)</b>	7.0
<b>Disc Diameter(Metric)</b>	17.5

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Flammability** UL 94 HB

**Operating Temperature (Metric)** -40°F to +221°F (-40°C to +105°C)

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 5000

**Package Quantity (Metric)** 5000

**Customs Number** 3926909988