

Specification Sheet

Part Number: 151-14312



Convolute Tubing Clip, 0.5" Max Bundle Diameter, .03"-.12" Panel Thick, PA66HIRHS, Black, 500/pkg

Article Number 151-14312

Type CTC13FT6

Color Black (BK)

Features & Benefits

- Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.
- Extended fir tree allows for a wide range of panel thicknesses.
- Fir tree design provides low insertion forces and high extraction forces.

Quantity Per bag

Product Description	Convuluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.
Short Description	Convuluted Tubing Clip, 0.5" Max Bundle Diameter, .03"-.12" Panel Thick, PA66HIRHS, Black, 500/pkg
Global Part Name	CTC13FT6-PA66HIRHS-BK
Fixation Method	Fir Tree
Variant	Clips
Width W (Imperial)	0.31
Width W (Metric)	8.0
Height H (Imperial)	1.0
Height H (Metric)	25.2
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	13.0
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.12
Panel Thickness Min (Metric)	0.75

Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Min (Imperial)	0.283
Mounting Hole Diameter D Max (Imperial)	0.275
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes

Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	1.2