

Specification Sheet

Part Number: 156-01798



2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 50mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn

Article Number 156-01798

Type T50RSADFTOVAL-SET

Color Black (BK)

Features & Benefits

- Bi-directional saddle allows for the securing of bundles perpendicular or parallel to mounting hole.
- HellermannTyton's 4x oval prevents bundle rotation while providing best-in-class installation and extraction resistance for four common oval sizes.

Quantity Per carton

Product Description	These two-piece fasteners offer a simple and versatile method of bundling and mounting cables up to 4.3" (110 mm) to a panel up to 6.0 mm thick using an oval hole. The fir tree will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be oriented in the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.
Short Description	2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 50mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn
Global Part Name	T50RSADFTOVAL-SET-PA66HS/PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	15.35
Length L (Metric)	390.0
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.694

Width W (Metric)	17.63
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.787
Height H (Metric)	20.0
Mounting Hole Diameter D (Imperial)	0.24 " X 0.48 " 0.26 " X 0.49 " 0.26 " X 0.51 " 0.28 " X 0.47
Mounting Hole Diameter D (Metric)	6.5 x 13.0 mm 6.2 x 12.2 mm 6.5 x 12.5 mm 7.0 x 12.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHSUV
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C) -40°F to +257°F (-40°C to +125°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	3000

Package Quantity (Metric)

3000

Customs Number

3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)