

## Specification Sheet

Part Number: 156-02280



MOC Clip to MOC Clip, 5 mm, 5 mm, PA66HIRHSUV, Black, 500/ctn

<b>Article Number</b>	156-02280
<b>Type</b>	MOC5FMOC5M
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.</li><li>• Controlled flex and angled entry promote easy installation.</li><li>• Independent rotation allows for adjustable routing orientation.</li></ul>
<b>Quantity Per</b>	carton
<b>Product Description</b>	The MOC to MOC is a rotatable dual routing clip that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.
<b>Short Description</b>	MOC Clip to MOC Clip, 5 mm, 5 mm, PA66HIRHSUV, Black, 500/ctn

<b>Global Part Name</b>	MOC5FMOC5M-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	0.95
<b>Length L (Metric)</b>	24.1
<b>Variant</b>	Clip to Clip
<b>Bundle Diameter Min (Imperial)</b>	0.16
<b>Bundle Diameter Min (Metric)</b>	4.0
<b>Bundle Diameter Max (Imperial)</b>	0.22
<b>Bundle Diameter Max (Metric)</b>	5.5
<b>Height H (Imperial)</b>	0.43
<b>Height H (Metric)</b>	10.8
<b>Depth D (imperial)</b>	0.39
<b>Depth D (metric)</b>	10.0
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV

<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	1.01
<b>Weight (Imperial)</b>	0.04