

## Specification Sheet

Part Number: 156-02283



MOC Clip to MOC Clip, 5 mm, 8 mm, PA66HIRHSUV, Black, 2000/ctn

**Article Number**

156-02283

**Type**

MOC5FMOC8M

**Color**

Black (BK)

**Features & Benefits**

- Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Controlled flex and angled entry promote easy installation.
- Independent rotation allows for adjustable routing orientation.

**Quantity Per**

carton

**Product Description**

The MOC to MOC is a rotatable dual routing clip that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

|                                       |  |
|---------------------------------------|--|
| <b>Short Description</b>              | MOC Clip to MOC Clip, 5 mm, 8 mm, PA66HIRHSUV, Black, 2000/ctn           |
| <b>Global Part Name</b>               | MOC5FMOC8M-PA66HIRHSUV-BK  |
| <b>Length L (Imperial)</b>            | 1.10   |
| <b>Length L (Metric)</b>              | 27.9   |
| <b>Variant</b>                        | Clip to Clip   |
| <b>Bundle Diameter Min (Imperial)</b> | 0.16   |
| <b>Bundle Diameter Min (Metric)</b>   | 4.0  |
| <b>Bundle Diameter Max (Imperial)</b> | 0.22   |
| <b>Bundle Diameter Max (Metric)</b>   | 5.5  |
| <b>Height H (Imperial)</b>            | 0.60   |
| <b>Height H (Metric)</b>              | 15.2   |
| <b>Depth D (imperial)</b>             | 0.39   |
| <b>Depth D (metric)</b>               | 10.0   |
| <b>Material</b>                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Material Shortcut</b>              | PA66HIRHSUV                       |
| <b>Flammability</b>                   | UL 94 HB                          |
| <b>Halogen free</b>                   | Yes                               |
| <b>Operating Temperature (Metric)</b> | -40°F to +230°F (-40°C to +110°C) |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 2000                              |
| <b>Package Quantity (Metric)</b>      | 2000                              |
| <b>Customs Number</b>                 | 3926909988                        |
| <b>Weight (Metric)</b>                | 1.28                              |
| <b>Weight (Imperial)</b>              | 0.05                              |