

## Specification Sheet

Part Number: 156-02313



MOC Clip to MOC Clip, 7 mm, 22 mm, PA66HIRHSUV, Black, 2000/ctn

**Article Number** 156-02313

**Type** MOC7FMOC22M

**Color** Black (BK)

**Features & Benefits**

- Patented retention design features inverted retaining legs, narrow opening and circular retainer to prevent inadvertent disengagement.
- Controlled flex and angled entry promote easy installation.
- Independent rotation allows for adjustable routing orientation.

**Quantity Per** carton

**Product Description**

The MOC to MOC is a rotatable dual routing clip that keeps two routings secured and separated. A swivel coupler allows them to rotate independently of each other.

|                                       |  |
|---------------------------------------|--|
| <b>Short Description</b>              | MOC Clip to MOC Clip, 7 mm, 22 mm, PA66HIRHSUV, Black, 2000/ctn          |
| <b>Global Part Name</b>               | MOC7FMOC22M-PA66HIRHSUV-BK   |
| <b>Length L (Imperial)</b>            | 1.87   |
| <b>Length L (Metric)</b>              | 47.5   |
| <b>Variant</b>                        | Clip to Clip   |
| <b>Bundle Diameter Min (Imperial)</b> | 0.24   |
| <b>Bundle Diameter Min (Metric)</b>   | 6.0  |
| <b>Bundle Diameter Max (Imperial)</b> | 0.31   |
| <b>Bundle Diameter Max (Metric)</b>   | 8.0  |
| <b>Height H (Imperial)</b>            | 1.44   |
| <b>Height H (Metric)</b>              | 36.5   |
| <b>Depth D (imperial)</b>             | 0.47   |
| <b>Depth D (metric)</b>               | 12.0   |
| <b>Material</b>                       | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Material Shortcut</b>              | PA66HIRHSUV                       |
| <b>Flammability</b>                   | UL 94 HB                          |
| <b>Halogen free</b>                   | Yes                               |
| <b>Operating Temperature (Metric)</b> | -40°F to +230°F (-40°C to +110°C) |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 2000                              |
| <b>Package Quantity (Metric)</b>      | 2000                              |
| <b>Customs Number</b>                 | 3926909988                        |
| <b>Weight (Metric)</b>                | 4.12                              |
| <b>Weight (Imperial)</b>              | 0.15                              |