## HellermannTyton

## **Specification Sheet**

Part Number: 156-02630



Article Number 156-02630

Type IRCBFT9LG

Color Black (BK)

**Features & Benefits** 

• One-piece ratchet closure allows for easy installation during pre- or final assembly. • Easy release feature simplifies quick adjustments and maintenance. • Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out. • High-performing round fir trees mean no additional fastener is needed for mounting.

Quantity Per bag

_				_				
Pı	n	du	rt.	D	esc	rin	tic	۱n

The In-line Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

**Short Description** 

In-Line Ratchet Clamp, 0.50" - 0.77" Bundle Dia, FT9LG,

PA66HIRHSUV, Black, 250/ctn

**Global Part Name** 

IRCBFT9LG-PA66HIRHSUV-BK

100.0

Minimum Tensile Strength (Imperial)

Minimum Tensile Strength (Metric) 445.0

Length L (Imperial) 1.37

Length L (Metric) 34.8

**Fixation Method** Fir tree for round holes

Width W (Imperial) 1.37

Width W (Metric) 34.9

**Bundle Diameter Min (Imperial)** 0.50

Bundle Diameter Min (Metric) 12.70

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.56
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.50
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	12.7
Mounting Hole Diameter D (Imperial)	0.35
Mounting Hole Diameter D (Metric)	9.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material  Material Shortcut	•
	(PA66HIRHSUV)
Material Shortcut	(PA66HIRHSUV) PA66HIRHSUV
Material Shortcut Flammability	(PA66HIRHSUV)  PA66HIRHSUV  UL 94 HB
Material Shortcut  Flammability  Operating Temperature (Metric)	(PA66HIRHSUV)  PA66HIRHSUV  UL 94 HB  -40°F to +221°F (-40°C to +105°C)

Package Quantity (Metric)	250			
© 2020 HellermannTyton. All Rights I	Reserved. Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions