

## Specification Sheet

Part Number: 157-00197



1-Pc Cable Tie/Offset Fir Tree w/Disc, 25 mm, FT6, 8" Tie, 50lb Tensile, PA66HIRHSUV, Black, 500/pkg

**Article Number** 157-00197

**Type** T50ROSFT6S25SO

**Color** Black (BK)

### Features & Benefits

- One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.
- The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.
- The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Quantity Per** carton

<b>Product Description</b>	HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes. The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.
<b>Short Description</b>	1-Pc Cable Tie/Offset Fir Tree w/Disc, 25 mm, FT6, 8" Tie, 50lb Tensile, PA66HIRHSUV, Black, 500/pkg
<b>Global Part Name</b>	T50ROSFT6S25SO-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	9.5
<b>Length L (Metric)</b>	242.2
<b>Offset Length(Imperial)</b>	0.98
<b>Offset Length(Metric)</b>	25.0
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Width W (Imperial)</b>	0.20
<b>Width W (Metric)</b>	5.1

<b>Bundle Diameter Min (Imperial)</b>	0.08
<b>Bundle Diameter Min (Metric)</b>	2.0
<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.15
<b>Panel Thickness Min (Metric)</b>	0.60
<b>Panel Thickness Max (Metric)</b>	3.75
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.27
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.27
<b>Mounting Hole Diameter D Max (Metric)</b>	6.9
<b>Disc Diameter (Imperial)</b>	0.75

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

<b>Material Shortcut</b>	PA66HIRHSUV
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.