

Specification Sheet

Part Number: 157-00350



Offset Fir Tree Cable Tie, B Series, 12.5mm Offset, 50mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn

Article Number 157-00350

Type T50ROSM10SO12.5B

Color Black (BK)

Features & Benefits

- 12.5 mm offset tie with fir tree secures bundles away from obstructions, heat or sources of abrasion.
- Versatile fir tree provides low insertion effort yet delivers exceptional retention strength in both an 8 mm and M10 threaded hole.
- B series tie secures bundles down below mounting surfaces.
- 50lb rated tie secures bundles up to 50 mm.

Quantity Per carton

Product Description	Offset Cable Ties route and position wire and cable bundles away from a mounting hole. The offset bar between the fir tree and cable tie strap provides a robust and cored-out design to eliminate any potential bending of the wire or cable assembly once installed. The combination of 12.5 mm and 25 mm offset distances and various fir tree sizes offer coverage for a majority of industry offset routing applications. The outside serrations of the tie strap prevent damage to soft or delicate bundles. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution.
Short Description	Offset Fir Tree Cable Tie, B Series, 12.5mm Offset, 50mm Max Bundle, PA66HIRHSUV, Black, 3000/ctn
Global Part Name	T50ROSM10SO12.5B-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.52
Length L (Metric)	216.4
Offset Length(Imperial)	0.50
Offset Length(Metric)	12.5
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No

Width W (Imperial)	0.19
Width W (Metric)	5.1
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Cable Ties	MK3PNSP2;MK3SP;MK6;MK7HT;MK7P;MK20;MK21;EVO7;EVO9
Height H (Imperial)	0.83
Height H (Metric)	21.0
Depth D (metric)	17
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.24
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Metric)	7.6 - 8.4 mm M10 x 1.50
Disc Diameter(Metric)	17.0
Disc Diameter (Imperial)	.67

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
Halogen free	No
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)