

Specification Sheet

Part Number: 157-00358



Standoff Fir Tree Cable Tie, 25mm standoff, 6.5mm Hole, 8" Tie, 50lb, PA66HIRHSUV, Black, 3000/ctn

Article Number 157-00358

Type T50ROSFT1025SO

Color Black (BK)

Features & Benefits

- 1-Piece cable tie and fir tree mount offers a simple method to bundle and fasten cables to panels with thickness up to 6.0 mm.
- Robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 10 mm hole.
- 8 inch outside serrated tie with low profile head design provides security for bundles up to 50 mm.
- 25 mm stand off on cable tie creates an alternate solution when an offset fastening option is required directly above the hole away from the mounting panel.

Quantity Per carton

Product Description	Offset Cable Ties route and position wire and cable bundles away from a mounting hole. The offset bar between the fir tree and cable tie strap provides a robust and cored-out design to eliminate any potential bending of the wire or cable assembly once installed. The combination of 12.5 mm and 25 mm offset distances and various fir tree sizes offer coverage for a majority of industry offset routing applications. The outside serrations of the tie strap prevent damage to soft or delicate bundles. One-piece mounting ties offer a complete solution by both bundling cable and at the same time providing a mounting solution.
Short Description	Standoff Fir Tree Cable Tie, 25mm standoff, 6.5mm Hole, 8" Tie, 50lb, PA66HIRHSUV, Black, 3000/ctn
Global Part Name	T50ROSFT1025SO-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	9.5
Length L (Metric)	242.3
Offset Length(Imperial)	0.98
Offset Length(Metric)	25.0
Fixation Method	Fir Tree
Identification Plate Position	none
Releasable Closure	No

Width W (Imperial)	0.44
Width W (Metric)	11.3
Bundle Diameter Min (Imperial)	0.07
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.96
Bundle Diameter Max (Metric)	50.0
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.39
Mounting Hole Diameter D (Metric)	10.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988
Content Unit(BMEcat)	pcs.