

Specification Sheet

Part Number: 155-30602



Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg

Article Number	155-30602
Type	T50SSBS5OT-E
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Design gives quick and easy assembly by hand without the need for tools.• Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts.• Design provides low insertion force and high extraction force.
Quantity Per	bag
Product Description	The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.

Short Description	Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg
Global Part Name	T50SSBS5OT-E-PA66HS-BK
Minimum Tensile Strength (Imperial)	45.0
Minimum Tensile Strength (Metric)	200
Length L (Imperial)	6.0
Length L (Metric)	160
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0

Bundle Diameter Max (Imperial)	1.4
Bundle Diameter Max (Metric)	35.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.35
Stud Length Max (Imperial)	0.65
Stud Length Max (Metric)	16.5
Stud Diameter (Metric)	5.0 mm
Stud Diameter (Imperial)	0.2
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes

Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	2.3