

Specification Sheet

Part Number: 161-05088



Spiralwrap Protective Sheathing, 0.88" Diameter, Polyamide, Black, 500ft/roll

Article Number 161-05088

Type 4.5N0H

Color Black (BK)

Features & Benefits

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

Quantity Per reel

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

| | |
|---------------------------------------|---|
| Short Description | Spiralwrap Protective Sheathing, 0.88" Diameter, Polyamide, Black, 500ft/roll |
| Global Part Name | 4.5N0H-PA6-BK |
| Length L (Imperial) | 500.0 |
| Length L (Metric) | 152.4 |
| Variant | Spiral Binding |
| Bundle Diameter Min (Imperial) | 0.5 |
| Bundle Diameter Min (Metric) | 12.7 |
| Bundle Diameter Max (Imperial) | 5.0 |
| Bundle Diameter Max (Metric) | 127.0 |
| Diameter D (imperial) | 0.75 |
| Diameter D (metric) | 19.05 |
| Nominal Diameter (Imperial) | 0.88 |
| Nominal Diameter (Metric) | 22.23 |
| Wall Thickness WT (Imperial) | 0.032 |
| Wall Thickness WT (Metric) | 0.81 |

| | |
|---------------------------------------|-----------------------------------|
| Material | Polyamide 6 (PA6) |
| Material Shortcut | PA6 |
| Flammability | Self-Extinguishing |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +250°F (-40°C to +121°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 500 |
| Package Quantity (Metric) | 152.40 |
| Customs Number | 3926909988 |