HellermannTyton

Specification Sheet

Part Number: 166-90506



HelaGuard Non-Metallic IP65 Compression Fitting, Straight, NPT Thread, 2.0" Dia., Black, 1/pkg

| Article Number | 166-90506 |
|---------------------|--|
| Туре | PSR200-S-2000 |
| Color | Black (BK) |
| Features & Benefits | • External NPT thread provides a secure connection. • Twist-on installation makes future access fast and easy. • Internal spigot design helps ease threading of fitting onto conduit. • All-around "teeth" attach firmly to conduit and deliver a high extraction force. • Durable nylon material has high resistance to salts, oils, weak acids and solvents. • IP65 rating for protection against wind, dirt and low pressure jets of water from all directions. |
| Quantity Per | pack |

| Product Description | Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits and tubing. |
|--------------------------------|--|
| Short Description | HelaGuard Non-Metallic IP65 Compression Fitting, Straight, NPT Thread, 2.0" Dia., Black, 1/pkg |
| Global Part Name | PSR200-S-2000-PA66-BK |
| Length L (Imperial) | 2.2 |
| Length L (Metric) | 56.0 |
| Outside Diameter OD(Imperial) | 2.99 |
| Outside Diameter OD(metric) | 76.0 |
| Nominal Diameter (Imperial) | 2.5 |
| Nominal Diameter (Metric) | 63 |
| | |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Operating Temperature (Metric) | -40°F to +248°F (-40°C to +120°C) |
| ROHS Complaint | Yes |

Package Quantity(Imperial) 1

Package Quantity (Metric)

Customs Number

3926909988

1

© 2020 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions