

Specification Sheet

Part Number: 169-60024



Convoluted Tubing, Unslit, .63" Dia, PA6, Black with Gray Stripe, 700ft/carton

Article Number	169-60024
Type	CTN580UNSLIT
Color	Black with Gray Stripe (BKSTGY)
Features & Benefits	<ul style="list-style-type: none">• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture• Tubing protects cables and wires against automotive fluids, vibration wear• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight
Quantity Per	carton

Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Unslit, .63" Dia, PA6, Black with Gray Stripe, 700ft/carton
Global Part Name	CTN580UNSLIT-PA6-BK
Length L (Imperial)	700.0
Length L (Metric)	213.4
Variant	Unslit
Inner Diameter D (Imperial)	0.639
Inner Diameter D (Metric)	16.23
Diameter D (imperial)	0.837
Diameter D (metric)	21.26
Outside Diameter OD(Imperial)	0.837
Outside Diameter OD(metric)	21.26
Nominal Diameter (Imperial)	0.63

Nominal Diameter (Metric)	16.00
Wall Thickness WT (Imperial)	0.005
Wall Thickness WT (Metric)	0.127
Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	700
Package Quantity (Metric)	213.4
Customs Number	3926909988