# HellermannTyton

## 211-60009

|                  | Article Number: 211-60009<br>P Clamp, .39" Width, .69" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg |
|------------------|--|
|                  |  |
| Download drawing | wnload spec sheet  |
|                  |  |
| Base Data        |  |

# Local Order Number211-60009TypeH10PColorBlack (BK)Features and Benefits·P-Clamps easily guide and locate wire and cables up to 1" in diameter.<br/>· Designed with a radiused edge to prevent chaffing and cutting into insulation.Product DescriptionHellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge<br/>to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.Short DescriptionP Clamp, .39" Width, .69" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

### **Product Dimensions**

| Fixation Method  | screw-hole |  |
|--|------------|--|
| Variant  | Closed     |  |
| Width W (Imperial)                                       | 0.39 "     |  |
| Width W (Metric)   | 10.0 mm    |  |
| Bundle Diameter Max. (Imperial)                          | 0.69 "     |  |
| Bundle Diameter Max. (Metric)                            | 17.5 mm    |  |
| Mounting Hole Diameter D (Imperial)                      | 0.17 "     |  |
| Mounting Hole Diameter D (Metric)                        | 4.2 mm     |  |
| Nominal Diameter (Imperial)                              | 11/16 "    |  |
| Nominal Diameter (Metric)                                | 17.5 mm    |  |
| Wall Thickness WT (Metric)                               | 1.5 mm     |  |
| Mounting Hole Centers (Imperial)                         | 0.67 "     |  |
| Mounting Hole Diameter D Max.                            |            |  |
| (Metric)<br>Mounting Hole Diameter D Min. (Metric)4.2 mm |            |  |

### Logistics and Packaging

Quantity PerpiecesPackage Quantity (Metric)100 PiecesCarton Quantity1500 PiecesWeight (Metric)1.3 kg

### **Material and Specifications**

 Material Shortcut
 PA66HS

 Flammability
 UL94 V2

 Operating Temperature
 -40°F to +221°F (-40°C to +105°C)

 ROHS Compliant
 Yes

© HellermannTyton 2015