

Specification Sheet

Part Number: SSU20-25M



HelaGuard Metallic Conduit, Extra Flexible, 0.50" (20mm) Dia, SS316, Metal, 82 ft/reel

Article Number 166-90836

Type SSU20-25M

Color Metal (ML)

Features & Benefits

- Stainless steel construction is highly resistant to rust and corrosion.
- Inherently low fire hazard material can withstand extreme temperature conditions.
- Highly durable spiral metallic conduit provides extra flexibility along with a high degree of compression, tensile and impact strength.
- Provides ingress protection performance to IP40 when used with FU-M style fittings.
- Tight bend radius for use in installations requiring constant movement or vibration.

Quantity Per reel

Product Description	A highly flexible stainless steel conduit used in constrained spaces and highly corrosive environments. SSU conduit is inherently low fire hazard, provides high mechanical strength and is anti-static. Designed for use where an extra flexible stainless steel conduit is needed in machinery, instrumentation and security within harsh environments or extreme temperature conditions. Use with FU-M series metallic fittings for IP40 ingress ratings or FSU-E conduit endcap inserts for a smooth entry point into conduit.
Short Description	HelaGuard Metallic Conduit, Extra Flexible, 0.50" (20mm) Dia, SS316, Metal, 82 ft/reel
Global Part Name	SSU20-25M-SS316-SR
Length L (Imperial)	82.0
Length L (Metric)	25.0
Inner Diameter D (Imperial)	0.67
Inner Diameter D (Metric)	16.9
Outside Diameter OD(Imperial)	0.80
Outside Diameter OD(metric)	20.4
Nominal Diameter (Imperial)	0.5
Nominal Diameter (Metric)	20
Material	Stainless Steel (SS316)

Material Shortcut	SS316
Flammability	Self-Extinguishing
Operating Temperature (Metric)	-148°F to +752°F (-100°C to +400°C)
Package Quantity(Imperial)	82.0
Package Quantity (Metric)	25.0
Customs Number	8307100000