



- Notes
- ① Applicable crimping contact:
 Contact No.1 to 11 : RP13A-SC-222(Applicable wire : AWG #24 to 28)
 Contact No.12 to 13 : RP13A-SC-212(Applicable wire : AWG #18 to 22)
 - 2 Applicable crimp contact crimping tool : RP13A-TC-01(CL150-0070-0)
 Applicable crimp contact extraction tool : RP13A-SC-TP(CL150-0022-8)
 - ③ The recommended tightening torque of Ref.No. ⑥ shell be 0.2N·m.
 - 4 This product is delivered disassemble.
 - 5 The cable pull and twisting strength and other characteristics may differ.
 Depending on the cable structure. please confirm before the use.

4	BRASS			7	PVC	(BLACK)	
3	POLYCARBONATE	(BLACK) UL94V-0		6	BRASS	ZINC PLATING BLACK CHROMETE TREATMENT (TRIVALENT CHROMIUM) JIS B 1111 M2X0.4X4	
2	POLYCARBONATE	(BLACK) UL94V-0		5	STEEL	NICKEL PLATING	
1	POLYCARBONATE	(BLACK) UL94V-0					
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS

UNITS mm		SCALE 2 : 1	COUNT ① 1	DESCRIPTION OF REVISIONS DIS-C-00001211	DESIGNED MM. ISHII	CHECKED EJ. KUNII	DATE 16.10.17
HRS HIROSE ELECTRIC CO., LTD. APPROVED : MR. YOSHIDA 05.01.05 CHECKED : MO. SATOH 05.01.05 DESIGNED : YH. YAMADA 05.01.05 DRAWN : YH. YAMADA 05.01.05				DRAWING NO. EDC4-009810-71 PART NO. RP13A-12PA-13SC(71) CODE NO. CL113-0182-4-71			