

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDITY RANGE	△85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ5.8~6.8
	CURRENT		VOLTAGE	

### SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

### CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△ 2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09. 12. 14

<b>REMARK</b> △ THIS PRODUCT SHALL BE MATED WITH DH3 * B-17S, IT APPLIES TO DH3*B-17S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	AO. SUZUKI	09. 04. 22
	CHECKED	KN. ICHIKAWA	09. 04. 22
	DESIGNED	MO. SHIMOYAMA	09. 04. 21
	DRAWN	MO. SHIMOYAMA	09. 04. 21

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126852-00
--	-------------	----------------

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH-17-CT1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0039-7-00	△ 1/1