

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD | | | | | |
|--|---------------------------------------|--------------------------|--|---------------------------|----------|
| RATING | OPERATING TEMPERATURE RANGE | -25°C TO +85°C | STORAGE TEMPERATURE RANGE | -25°C TO +60°C | |
| | VOLTAGE | | APPLICABLE CABLE | CABLE DIAMETER : φ8.3~9.3 | |
| | CURRENT | | | | |
| SPECIFICATIONS | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | | X | X |
| | | | | | |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
| △ | | | | | |
| REMARK | | | APPROVED | A0. SUZUKI | 09.05.11 |
| THIS PRODUCT SHALL BE MATED WITH DH30B-37S, IT APPLIES TO DH30B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402. | | | CHECKED | KN. ICHIKAWA | 09.05.11 |
| | | | DESIGNED | MO. SHIMOYAMA | 09.05.11 |
| | | | DRAWN | MO. SHIMOYAMA | 09.05.11 |
| | | | Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | |
| HRS | SPECIFICATION SHEET | | PART NO. | DH-37-CT2B | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL244-0049-0-00 | △ 1/1 |