

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ9.1~10.1
	CURRENT		VOLTAGE	
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09.12.14
REMARK		APPROVED	AO. SUZUKI	09.04.28
THIS PRODUCT SHALL BE MATED WITH DH3*B-51S, IT APPLIES TO DH3*B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.  Unless otherwise specified, refer to JIS C 5402.		CHECKED	KN. ICHIKAWA	09.04.28
		DESIGNED	MO. SHIMOYAMA	09.04.28
		DRAWN	MO. SHIMOYAMA	09.04.28
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-126870-00	
	SPECIFICATION SHEET	PART NO.	DH-51-CT1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0044-7-00	1/1