

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	CABLE DIAMETER : φ9.1~10.1	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK			APPROVED	A0. SUZUKI	09.05.11
THIS PRODUCT SHALL BE MATED WITH DH30B-51S, IT APPLIES TO DH30B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.			CHECKED	KN. ICHIKAWA	09.05.11
			DESIGNED	MO. SHIMOYAMA	09.05.11
			DRAWN	MO. SHIMOYAMA	09.05.11
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
HRS	SPECIFICATION SHEET		PART NO.	DH-51-CT2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0050-0-00	△ 1/1