

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ 9.1~10.1
	VOLTAGE			
	CURRENT			
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△ 2	DIS-E-00002570	TS. ITO	TU. TANIGUCHI	20191007
REMARK		APPROVED	KN. ICHIKAWA	20091117
△ THIS PRODUCT SHALL BE MATED WITH DH40-51S OR DH3 * B-51S, IT APPLIES TO DH40-51S OR DH3 * B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.		CHECKED	KN. ICHIKAWA	20091117
		DESIGNED	MO. SHIMOYAMA	20091117
△ Unless otherwise specified, refer to IEC 60512.		DRAWN	TM. ONO	20091116
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-126589-00-00	
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	DH-51-CV1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0012-0-00	△ 1/1